



PRODUCT NUMBER: 2058685

CRYOGENIC

Protection against small drops of liquid gas up to -170°C.

Overview

Reference Number

2058685

Product Type

Gloves

Range

Specific Protection

Brand

Honeywell

Brand formerly known as

SPERIAN

Industry

- Chemical Industries
- Petro-chemical

Product Use

Protection against small drops of liquid gas up to -170°C.

Features & Benefits

Feature

Water-repellent silicone cowhide grain leather glove

Fully lined with 2 aluminium/fleece layers

Gunn cut, winged thumb, crispin type

Reinforcement between thumb and index

200 mm split leather cuff

Velcro® adjustment strap on side of the palm

Benefit

COMFORT

The US assembly, the winged thumb and flexibility of the materials used make this glove anatomical, thus providing excellent comfort.

The Velcro fastening tab gives the glove good support.

RESISTANCE

CRYOGENIC - 2058685

The silicone cowhide grain leather ensures good flexibility, even at a low temperature as well as water repellence and good mechanical protection.

Its polar double insulation offers outstanding protection against the cold and rays.

The reinforcement between the thumb and index finger increases the glove's mechanical resistance and durability by strengthening the areas of wear.

HYGIENE

The hide cuff offers good forearm protection against mechanical hazards and limits any risk of intrusion.

Technical Description

Description

CE CATEGORY : II Intermediary risks
 In accordance with standards :
 EN 420-2003 EEC Basic standards
 EN 388-2003 Mechanical Hazards
 EN 511-2006 Cold protection

CHARACTERISTICS :

Water-repellent silicone cowhide grain leather glove
 Fully lined with 2 aluminium/fleece layers
 Gunn cut, winged thumb, crispin type
 Reinforcement between thumb and index
 20 cm split leather cuff
 Velcro® adjustment strap on side of the palm

Product Technology

Cut and Sewn

Coating Type

Leather

Thickness

1.1/1.3 mm

Harmlessness

In conformity with the European standards

Dexterity

Class 5

Sizes

9 to 11

EN 388 - Mechanical Hazards Abrasion Resistance

Abrasion resistance	3
Cutting resistance (Coupe test)	2
Tear resistance	2
Puncture resistance	2

EN 511- Protection in cold temperatures:

Resistance to conductive cold	2
Resistance to contact cold	2
Water permeability	0

Packaging Label

Tagging

CE HONEYWELL
 2058685 XX
 EN 420
 EN 388 : 3222
 EN 511 : 220

Certifications

EC Category PPE

2

EC Certificate Number

0075/797/162/01/09/0001

EC Attestation

 EC Attestation

EC Attestation Number

0075/797/162/01/09/0001

Additional Information

User Manual

UI 105

User Information Sheet

105

Maintenance

Storage Information

Minimum packaging 1 pair.

Cartons of 25 pairs.

Care Instructions

In order to keep its properties, this article should not be cleaned.