



PRODUCT NUMBER: 2232070
ARATHERMA NOMEX® HEAVY

Protection against thermal hazards up to 250°C. For handling in a dry and hot atmosphere of sharp parts.

Honeywell

Overview

Reference Number

2232070

Product Type

Gloves

Range

Thermal Protection

Line

Heat

Brand

Honeywell

Brand formerly known as

SPERIAN

Industry

- Industry
- Automotive and Part Manufacturer
- Glass Industries
- Iron and steel industry

Product Use

Protection against thermal hazards up to 250°C. For handling in a dry and hot atmosphere of sharp parts.

Features & Benefits

Feature

100% Nomex® seamless glove

Lined with a seamless

Cotton glove

Ambidextrous

Benefit

COMFORT

The knitting technique helps to obtain a glove that conforms snugly to the hand and good dexterity.

The glove offers maximum comfort and added sturdiness.

The cotton interlock lining strengthens the glove's mechanical performance while absorbing perspiration.

The glove is ambidextrous and thus more cost-effective.

The glove's relative thickness (gauge 13) enables it to absorb shocks, making it suitable for the handling of heavy objects.

RESISTANCE

The NOMEX® fibre pills only a little and ensures good heat resistance for removing dishes from the oven... up to 250C.

HYGIENE

White in colour, it is compatible with the agrifood industry while enhancing hygiene and cleanliness.

Technical Description

Description

CE CATEGORY : II Intermediary risks

In accordance with standards :

EN 420-03 EEC Basic standards

EN 388-03 Mechanical Hazards

EN 407-04 Thermal hazards

CHARACTERISTICS :

NOMEX knitted glove

Lined with 100 % knitted glove

Oversewed knitted wrist

Ambidextrous

Product Technology

Knitted

Gauge

13

Coating Type

Nomex® and cotton

Length

26,5 cm

Harmlessness

In conformity with the European standards

Dexterity

Class 2

Sizes

7 and 9

EN 407 - Heat and/or Fire

Behaviour and/or fire	4
Resistance to contact heat	3
Resistance to convective heat	X
Resistance to radiant heat	X
Resistance to small metal splashes	X
Resistance to molten metal splashes	X

EN 388 - Mechanical Hazards Abrasion Resistance

Abrasion resistance	1
Cutting resistance (Coupe test)	4
Tear resistance	4
Puncture resistance	X

Packaging Label

Tagging

CE HONEYWELL
2232070 XX
EN 420
EN 388 : 144X
EN 407 : 43XXXX

Certifications

E.C. Declaration of Conformity

EC Category PPE

2

Quality Assurance

ISO 9001 / 2000

EC Certificate Number

0075/797/162/12/07/0435

EC Attestation

EC Attestation

EC Attestation Number

0075/797/162/12/07/0435

Additional Information

User Manual

UI 106

User Information Sheet

106

Maintenance

Storage Information

Minimum packaging 10 pairs.
Cartons of 50 pairs.

Care Instructions

In order to keep its properties, this article should not be cleaned.